

**Cable lubricating compound FOAM | Item no. 20522**

## SAFETY DATA SHEET

ACCORDING TO ANNEX II TO REACH - REGULATION 2020/878 AND TO ANNEX II TO UK REACH

### SECTION 1.

#### IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### 1.1 Product identifier

Cable lubricating compound FOAM 400 ml - 20522

##### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Intended use:** Electrical cable lubricant water based. Specific foam to reduce the friction during cable laying

##### 1.3 Details of the supplier of the safety data sheet

RUNPOTEC GmbH | Irlachstraße 31 | A-5303 Thalgau  
Tel.: +43-6235-20335 | Fax: +43-6235-20335-35  
office@runpotec.com | www.runpotec.com

##### 1.4 Emergency telephone number

Emergency information services / public advisory office:

AUSTRIA: Vergiftungsinformationszentrale der Gesundheit Österreich GmbH, Wien.

NOTRUF Tel.: 01 406 43 43 (von außerhalb Österreichs Tel.: +43 1406 43 43)

Switzerland: Tox Info Suisse, Freiestrasse 16, CH-8032 Zürich. Nationale 24h-Notfallnummer: 145

### SECTION 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### Hazard classification and indication:

Aerosol, category 3                      H229      Pressurised container: may burst if heated.

#### 2.2 Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:                      --

Signal words:                              Warning

Hazard statements:  
H229                                      Pressurised container: may burst if heated.

Precautionary statements:  
P210                                      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P251                                      Do not pierce or burn, even after use.  
P410+P412                              Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.  
0,90% by mass of the contents are flammable.

#### 2.3 Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.  
The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## **Cable lubricating compound FOAM | Item no. 20522**

### **SECTION 3. Composition/information on ingredients**

#### **3.1 Mixtures**

The product does not contain substances classified as being hazardous to human health or the environment pursuant to the provisions Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and supplements) in such quantities as to require the statement.

### **SECTION 4. First aid measures**

#### **4.1 Description of first aid measures**

No episodes of harm to the staff authorised to use the product have been reported. The following general measures should be adopted as necessary:

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Do not give anything by mouth to an unconscious person.

**EYES and SKIN:** Wash with plenty of water. In the event of persistent irritation, get medical advice/attention.

#### **4.2 Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Information not available

### **SECTION 5. Firefighting measures**

#### **5.1 Extinguishing media**

**SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular

#### **5.2 Special hazards arising from the substance or mixture**

**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

#### **5.3 Advice for firefighters**

**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **SECTION 6. Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### **6.2 Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

## Cable lubricating compound FOAM | Item no. 20522

### 6.3 Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1 Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

STORAGE CLASS TRGS 510 (GERMANY): 2B

STORAGE CLASS TRGS 510 (GERMANY): 2B

### 7.3 Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1 Control parameters

Regulatory References:

|     |             |                                                                                                                                                                                                                                           |
|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DEU | Deutschland | Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56             |
| DNK | Danmark     | Bekendtgørelse om grænseverdier for stoffer og materialer - BEK nr 1458 af 13/12/2019                                                                                                                                                     |
| ESP | España      | Límites de exposición profesional para agentes químicos en España 2021                                                                                                                                                                    |
| NOR | Norge       | Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255 |
| NLD | Nederland   | Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit                                                                     |
| SWE | Sverige     | Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)                                                                                                                           |
| SVN | Slovenija   | Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)                                                   |
|     | TLV-ACGIH   | ACGIH 2021                                                                                                                                                                                                                                |

| NITROUS OXIDE         |         |                   |     |                   |     |                        |
|-----------------------|---------|-------------------|-----|-------------------|-----|------------------------|
| Threshold Limit Value |         |                   |     |                   |     |                        |
| TYP                   | COUNTRY | TWA / 8 h         |     | STEL/15 min       |     | Remarks / Observations |
|                       |         | mg/m <sup>3</sup> | ppm | mg/m <sup>3</sup> | ppm |                        |
| TLV-ACGIH             |         | 90                | 50  |                   |     |                        |

**Cable lubricating compound FOAM | Item no. 20522****HEALTH - DERIVED NO-EFFECT LEVEL**

| DNEL / DMEL       |                      |                |               |                  |                    |                |               |                       |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|-----------------------|
|                   | Effects on consumers |                |               |                  | Effects on workers |                |               |                       |
| Route of exposure | Acute local          | Acute systemic | Chronic local | Chronic systemic | Acute local        | Acute systemic | Chronic local | Chronic systemic      |
| Inhalation        |                      |                |               |                  |                    |                |               | 183 mg/m <sup>3</sup> |

**TRIETHANOLAMINE**

| Threshold Limit Value |         |                   |     |                   |         |                        |
|-----------------------|---------|-------------------|-----|-------------------|---------|------------------------|
| TYP                   | COUNTRY | TWA / 8 h         |     | STEL/15 min       |         | Remarks / Observations |
|                       |         | mg/m <sup>3</sup> | ppm | mg/m <sup>3</sup> | ppm     |                        |
| AGW                   | DEU     | 1                 |     |                   |         | INHAL                  |
| MAK                   | DEU     | 1                 |     |                   |         | INHAL                  |
| TLV                   | DNK     | 3,1               | 0,5 |                   |         |                        |
| VLA                   | ESP     | 5                 |     |                   |         |                        |
| TLV                   | NOR     | 5                 |     |                   |         |                        |
| TGG                   | NLD     | 5                 |     |                   |         |                        |
| NGV/KGV               | SWE     | 5                 | 0,8 | 10 (C)            | 1,6 (C) | SKIN                   |
| MV                    | SVN     | 5                 |     |                   |         | INHAL                  |
| TLV-ACGIH             |         | 5                 |     |                   |         |                        |

**Legend:**

(C)= CEILING; INHAL= Inhalable Fraction; RESP= Respirable Fraction; THORA= Thoracic Fraction. VND= hazard identified but no DNEL/PNEC available; NEA= no exposure expected; NPI= no hazard identified; LOW= low hazard; MED= medium hazard; HIGH= high hazard.

**8.2 Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

**HAND PROTECTION**

None required.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type A filter combined with a type P filter should be worn (see standard EN 14387). Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## Cable lubricating compound FOAM | Item no. 20522

### SECTION 9. Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

| Properties                             | Value                    | Information          |
|----------------------------------------|--------------------------|----------------------|
| Appearance                             | foam spray               |                      |
| Colour                                 | white                    |                      |
| Odour                                  | little soap              |                      |
| Melting point / freezing point         | 0 °C                     |                      |
| Initial boiling point                  | not applicable           |                      |
| Boiling range                          | 100 °C                   |                      |
| Flammability                           | not flammable            |                      |
| Lower explosive limit                  | not available            |                      |
| Upper explosive limit                  | not available            |                      |
| Flash point                            | Combustion not sustained |                      |
| Auto-ignition temperature              | not available            |                      |
| Decomposition temperature              | not available            |                      |
| pH                                     | 7,5-8                    |                      |
| Kinematic viscosity                    | not available            |                      |
| Solubility                             | soluble in water         |                      |
| Partition coefficient: n-octanol/water | not available            |                      |
| Vapour pressure                        | 5 Bar                    | Temperature: = 20 °C |
| Density and/or relative density        | 1,07                     |                      |
| Relative vapour density                | not available            |                      |
| Particle characteristics               | not applicable           |                      |

#### 9.2 Other information

##### 9.2.1 Information with regard to physical hazard classes

AEROSOL

% flammable components: 0,9

FLAMMABLE LIQUIDS

Sustained combustibility: does not sustain combustion

##### 9.2.2 Other safety characteristics

Total solids (250°C / 482°F) 0 %

VOC (Directive 2010/75/EU) 7,00 % - 21,00 g/litre

VOC (volatile carbon) 3,31 % - 9,00 g/litre

Explosive properties not applicable

Oxidising properties not applicable

### SECTION 10. Stability and reactivity

#### 10.1 Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2 Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3 Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4 Conditions to avoid

Avoid overheating.

#### 10.5 Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

#### 10.6 Hazardous decomposition products

Information not available

## Cable lubricating compound FOAM | Item no. 20522

### SECTION 11. Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

METABOLISM, TOXICOKINETICS, MECHANISM OF ACTION AND OTHER INFORMATION  
Information not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE  
Information not available

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE  
Information not available

INTERACTIVE EFFECTS  
Information not available

ACUTE TOXICITY  
ATE (Inhalation) of the mixture: Not classified (no significant component)  
ATE (Oral) of the mixture: Not classified (no significant component)  
ATE (Dermal) of the mixture: Not classified (no significant component)

SKIN CORROSION / IRRITATION  
Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION  
Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION  
Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY  
Does not meet the classification criteria for this hazard class

CARCINOGENICITY  
Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY  
Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE  
Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE  
Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD  
Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1 Toxicity

Information not available

## Cable lubricating compound FOAM | Item no. 20522

### 12.2 Persistence and degradability

Information not available

### 12.3 Bioaccumulative potential

Information not available

### 12.4 Mobility in soil

Information not available

### 12.5 Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

### 12.7 Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1 Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

### 14.1 UN number or ID number

ADR/RID, IMDG, IATA: 1950

### 14.2. UN proper shipping name

ADR/RID: AEROSOLS

IMDG: AEROSOLS

IATA: AEROSOLS, NON-FLAMMABLE

### 14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.2 

IMDG: Class: 2 Label: 2.2 

IATA: Class: 2 Label: 2.2 

### 14.4. Packing group

ADR/RID, IMDG, IATA -

### 14.5 Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

**Cable lubricating compound FOAM | Item no. 20522**
**14.6 Special precautions for user**

|           |                      |                             |                                |
|-----------|----------------------|-----------------------------|--------------------------------|
| ADR /RID: | HIN - Kemler: --     | Limited Quantities: 1 L     | Tunnel restriction code: (E)   |
|           | Special Provision: - |                             |                                |
| IMDG:     | EMS: F-D, S-U        | Limited Quantities: 1 L     |                                |
| IATA:     | Cargo                | Maximum quantity:<br>150 Kg | Packaging instructions:<br>203 |
|           | Pass.                | Maximum quantity:<br>750 Kg | Packaging instructions:<br>203 |
|           | Special provision    | A98, A145, A167, A802       |                                |

**14.7 Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information**
**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

SEVESO CATEGORY - DIRECTIVE 2012/18/EC:

None

RESTRICTIONS RELATING TO THE PRODUCT OR CONTAINED SUBSTANCES PURSUANT TO ANNEX XVII TO EC REGULATION 1907/2006

Product

Point 40

Contained substance

Point 75

REGULATION (EU) 2019/1148 - ON THE MARKETING AND USE OF EXPLOSIVES PRECURSORS

Not applicable

SUBSTANCES IN CANDIDATE LIST (ART. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

SUBSTANCES SUBJECT TO AUTHORISATION (ANNEX XIV REACH)

None

SUBSTANCES SUBJECT TO EXPORTATION REPORTING PURSUANT TO (EC) REG. 649/2012:

None

SUBSTANCES SUBJECT TO THE ROTTERDAM CONVENTION:

None

SUBSTANCES SUBJECT TO THE STOCKHOLM CONVENTION:

None

HEALTHCARE CONTROLS:

Information not available

GERMAN REGULATION ON THE CLASSIFICATION OF SUBSTANCES HAZARDOUS TO WATER (AWSV, VOM 18. APRIL 2017)

WGK 1: Low hazard to waters

**15.2 Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## Cable lubricating compound FOAM | Item no. 20522

### SECTION 16. Other information

#### Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Aerosol 3      Aerosol, category 3  
 H229      Pressurised container: may burst if heated.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

**Cable lubricating compound FOAM | Item no. 20522**

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.